

Vendor HME Clear-Com
Model Eclipse HX

Date 1/4/2020
Version 12

AES67-2018 PICS Summary

Transport	☒ Multicast ☐ Unicast
QoS configuration	☐ Configurable markings with standard defaults ☒ Fixed standard markings ☐ Configurable, other defaults ☐ Other markings, not configurable
Sample rates	☒ 48 kHz ☐ 44.1 kHz ☐ 96 kHz
Packet times	☒ 1 ms ☒ 125 μ s ☐ 250 μ s ☐ 333 μ s ☐ 4 ms
PTP profiles	☐ IEEE1588 Default ☒ AES67 PTP Media ☐ IEEE 802.1AS (AVB)
SDP transport	☒ Manually ☒ SAP ☐ SIP ☐ Other (specify)
<i>Description</i>	
Discovery	☒ SAP ☐ mDNS ☐ NMOS IS-04 ☐ Other (specify)
<i>Description</i>	
Packet spacing (Transmitter)	☒ strict ☐ loose
Jitter buffer (Receiver)	☒ small ☐ large
SIP support	☐

Other interoperability disclosures

SMPTE ST 2110-30 support	☒
Other PTP profiles	☒ SMPTE ST 2059-2 ☐ Other (specify)
<i>Description</i>	