

AES-R19-2019

Vendor YAMAHA
Model Rio1608-D

Date 2020/03/09
Version 5.1

AES67-2018 PICS Summary

Transport

☒ Multicast ☐ Unicast

QoS configuration

- ☐ Configurable markings with standard defaults
- ☒ Fixed standard markings
- ☐ Configurable, other defaults
- ☐ Other markings, not configurable

Sample rates

☒ 48 kHz ☐ 44.1 kHz ☐ 96 kHz

Packet times

☒ 1 ms ☒ 125 μ s ☒ 250 μ s ☒ 333 μ s ☐ 4 ms

PTP profiles

☐ IEEE1588 Default ☒ AES67 PTP Media ☐ IEEE 802.1AS (AVB)

SDP transport

☒ Manually ☒ SAP ☐ SIP ☐ Other (specify)

Description

Manual configuration of SDP transport requires Dante Domain Manager

Discovery

☒ SAP ☐ mDNS ☐ NMOS IS-04 ☐ Other (specify)

Description

Packet spacing (Transmitter)

☒ strict ☐ loose

Jitter buffer (Receiver)

☒ small ☐ large

SIP support

☐

Other interoperability disclosures

SMPTE ST 2110-30 support

☐

Other PTP profiles

☐ SMPTE ST 2059-2 ☐ Other (specify)

Description