Project	IEEE 802 Executive Committee Study Group on TV White Spaces - ADHOC USE CASE SUB-GROUP
Title	ECSG ADHOC INTEROPERABILITY AND COEXISTENCE DISCUSSION
Date Submitted	2009-01-23
Source(s)	Contributor: Ivan Reede, Affiliation AmeriSys Inc. e-mail: i_reede@amerisys.com Contributor: exerprts and figures copied from document 09-0007-04-0000
Abstract	IEEE 802 ECSG on White Space interoperability vs coexistence
Purpose	To provide input to the ECSG a discussion platform to consider the possibility of interoperability and coexistence in the TVWS spectrum.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.
Patent Policy and Procedures	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: http://standards.ieee.org/guides/bylaws/sect6-7 , html#6> and http://standards.ieee.org/guides/opman/sect6.html#6.3 . Further information is located at http://standards.ieee.org/board/pat/pat-material.html and

802 Whitespace Interoperability and Coexsitence Discussion Seed

Purpose: to help the 802 EC SG to decide if it should recommend that 802 should aim toward interoperability or limit itself to simple coexistence between 802 stds in the TVW S

- There are winning factors for everybody
 - From the end-user point of view
 - From the standards point of view
 - From a manufacturer's point of view
 - For 802

- End-user point Win points
 - Roaming from one system (4W) to the next (100mW) may be desirable
 - Inter-operable standards would probably be better than simply coexisting standards
 - Single NIC use is simpler than having multiple NICs

- Standards Win points
 - Coexistence amongst inter-operable devices may be more natural
 - Spectrum sharing and access fairness may be enhanced
 - Common hardware across standards creates economies of scale
 - · Leveraging the contents of one standard to another may be simplified
 - Thereby reducing development costs and time to market for ensuing standards
 - Favor cohesive rather than maverick expansion

- Manufacturer's Win points
 - Added perceived value gives consumers an impetus to update their hardware
 - Drive sales via leveraging as rural areas are served by .11 and .22 networks
 - Create a larger unified consumer base

Allow economies of scale than a fragmented market provides

- For 802
 - Give a professional unified image of highly cohesive and extremely functional group
 - · Improve the <u>802</u> brand value simultaneously for all Working Groups

- A prime example
 - Most if not just about all 802.11 NICs have 802.11b and 02.11g
 - · It is to b expected that 802.11n NICs will have a,b,g and n support

- What would be required
 - Common PHY
 - · Muliti-mode MAC

