

# Making the Case for Open, Softwarized, Data-Driven 802.11 Networks

**Date:** 2022-03-08

Authors:

<b>Name</b>	<b>Affiliations</b>	<b>Address</b>	<b>Phone</b>	<b>email</b>
Francesco Restuccia	Northeastern University, WIOT Institute	360 Huntington Ave, Boston, MA 02215 USA	617-373-3655	frestuc@northeastern.edu

# **What is the current threat**

**Risk of doing things the way it is now**

**How a softwarized, data-driven 802.11 architecture  
will drive costs down**

# Emerging new markets

**Enhancement of existing 802.11 business models**

**Creation of new 802.11 business opportunities**

# What is the current threat?


# Strategy to improve 802.11 routers?

- Increase Bandwidth (2x)

160 MHz  
(802.11ax)

320 MHz  
(802.11be)


- Increase Spatial Streams (2x)




- For better performance? Is it really needed?
- No 802.11ac routers that do 8x8 MIMO! Why?

## Complexity of MIMO in Wi-Fi Systems

Optimal waveform generation requires the usage of **MU-MIMO** and **beamforming** techniques



8 x 8 @ 160 MHz, BM report is (486 subcarriers x 56 angles/subcarrier x 16 bits/angle) ~ **54.43 KB**  
 If BM reports are sent back every 10 ms, the airtime overhead is **435,456 / 0.01 ~ 43.55 Mbit/s**

- **Increasing complexity**
  - **Makes cost go UP!**
- 
- Routers are becoming **very expensive**
  - **With respect to a 802.11ac router**
    - A Wi-Fi 6E router is **~6x more expensive**
    - A tri-band Wi-Fi router is **~15x more expensive**


Ry Christ (CNET). Wi-Fi 6E routers are here, and we're not ready for them  
<https://www.cnet.com/home/internet/wi-fi-6e-routers-are-here-and-were-not-ready-for-them/>

**Threat:**  
**Fewer People Buy the  
New, Fancy, Expensive Routers**



# What's going on in the 5G/Cellular Community?


# The Open RAN (O-RAN) Paradigm



(1) Disaggregation of RAN **hardware** and **software**

(2) **RAN Intelligent Controller (RIC)** operating at different granularity levels

I need to stream **4K video** to **100 users** in **Times Square, NY** from **8pm to 9pm**



- Control is **hardware-** and **vendor-agnostic**, so software runs in any O-RAN compliant network
- Zero-touch AI-based control is **natively supported**,
  - best performance
  - self-adaptation

## **Advantages of Open, Virtualized Networks**

- 1. Interoperability reduces CAPEX (60%)**
- 2. Future-proof – no rip and replace infrastructure**
- 3. Easier maintenance results in reduced OPEX (65%)**
- 4. Faster deployments, higher throughput, coverage and capacity**

**O-RAN market is estimated to attain a revenue of USD 419.51 Million in 2021 and USD 21,371.47 Million in 2028, CAGR of 83.1%**

<https://www.researchnester.com/reports/open-radio-access-network-market/2781>

Parallel Wireless, “OpenRAN – 7 vital benefits for MNOs,” <https://www.parallelwireless.com/blog/openran-7-vital-benefits-for-mnos/>


**Apply the Same Concepts to Wi-Fi?**

**Do more with less antennas and BW  
(SW vs HW), yet more devices (unlicensed  
bands!)**

**Router costs can be contained  
(why? less complexity,  
less maintenance costs)**


## Apply the Same Concepts to Wi-Fi?

**Good performance with less costs!**  
**(People will choose 802.11**  
**and not 5/6G networks)**





# Emerging New Markets

# New Market: 802.11bf



- The research community has worked on these topics for ~10 years
- First “See Through Walls With Wi-Fi!” paper in 2013
- Extreme commercial potential, that’s why 802.11bf was created

# Problems: Generalization, Robustness





- **Trained and tested in different environments**
- **Performance does not generalize to different environments**
- **Clients may not buy the product if it's a one-trick pony**
- **Some Wi-Fi sensing devices have been shown to experience problems in actual deployments [1]**

[1] Christopher Null (TechHive). "Aura review: This home monitoring system is more trouble than it's worth." <https://www.techhive.com/article/583109/aura-review.html>, December 27, 2017.



# Better Performance Through Cooperation



- **Through CSI fusion, we are able to generalize among different environments**
- **Ultimately, more sales because the product satisfies the customer better!**

N. Bahadori, J. Ashdown, and F. Restuccia, "ReWiS: Reliable Wi-Fi Sensing Through Few-Shot Multi-Antenna Multi-Receiver CSI Learning," to appear in IEEE WOWMOM 2022. Preprint available at <https://arxiv.org/abs/2201.00869>

Today, it's **very hard**  
to extract CSI from routers

---


Tool	IEEE Std	Data points/CSI
CSI Tool [4]	802.11n	30
Atheros CSI Tool [8]	802.11n	56
Nexmon CSI [3]	802.11ac	up to 4096
AX-CSI [2]	802.11ax	up to 32768

---

CSI fusion techniques  
**are not supported** by today's  
802.11 standards

New companies that can be centered  
around CSI sensing are **hindered**

# New Market: AI-Driven Wi-Fi Offloading



- 5G will offload a whopping **71%** of its traffic to Wi-Fi by 2022
- Reduces **costs** for providers, and ultimately, for customers
- Improves service, so more **customer experience** and less **churning**

Claus Hetting, Cisco VNI predicts bright future for Wi-Fi,  
<https://wifinowglobal.com/news-and-blog/new-cisco-vni-numbers-predict-bright-future-for-wi-fi-towards-2022/>



# New Market: AI-Driven Wi-Fi Offloading

- **Exciting business opportunity**
  - Much cheaper for MNOs than deploying femtocells
  - Wi-Fi APs are ubiquitous in indoor settings
  - Networking-as-a-Service (NaaS)

- **Killer use cases:**


- Shopping Malls
- Stadiums
- Concerts
- ...
- Crowded Places



## Problem: Wi-Fi at Scale

- **Wi-Fi is not made for many users**
  - DL MU-MIMO is limited to **8** users in 802.11ax, **4** in 802.11ac
  - Maximum of **4** SS/user in 802.11ax, **2** SS/user in 802.11ac
- **Not scalable for these applications!**
  - More antennas, more BW is **not** the solution!
  - We cannot transform an **AP in a femtocell!**
  - We need **cost-effective** solutions

# Solution: Cooperative AI-Driven Wi-Fi Offloading



- Cheaper APs, but smarter (AI) and cooperative!
- Target: deploy more APs, bring complexity (and costs down)
- Sharing **spectrum** and **network information** with 5G networks

## To Summarize

**802 networks should adopt **open, softwarized, AI-driven** strategies to remain competitive**

**802 networks should learn to coexist with other technologies and **embed AI by design** into their architecture**



# How can the 802 RM evolve?




Figure 3—IEEE 802 RM for end stations

## Modules and Interfaces

- **Interfaces** for MAC control & monitoring (beams, modulation, coding, etc) and channel control (CSI)

- **Modules** for distributed & centralized control of MAC/PHY,
  - for current 802 network
  - across 802 networks
  - different networks (e.g., O-RAN)
- If **centralized**, interfaces from/to central controller (e.g., AP in Wi-Fi)
- **Interfaces** for radio control & monitoring (e.g., beams, modulation, coding, etc) and channel control (e.g., CSI)

**Thanks!**  
**Questions?**