

---

**Project: IEEE P802.15 Working Group for Wireless Personal Area Networks  
(WPANs)**

**Submission Title:** assigned comments for draft D2

**Date Submitted:** September 2010

**Source:** Sridhar Rajagopal [Samsung Electronics]

Address:

Contact Information: [sridhar.r@samsung.com]

**Re:**

**Abstract:** proposes comment resolutions for a set of CIDs

**Purpose:**

**Notice:** This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

**Release:** The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

## Comments for T-CIDs

38, 51, 63, 70, 72

## T-CID 38

### Suggested Remedy:

- Accept in principle - committee as asked Sridhar to bring forth a contribution that goes through clauses 4 and 5 individually addressing each instance of the acronym MPDU, making a disposit recommendation.

### Instruction to editor

- Accept changes to MPDU to PSDU per next 2 slides

## T-CID 38 : MPDU entries in clause 4

4.4.2, pg 10, line 24 – ok

4.5.4.2, pg 18, line 47 – ok

4.5.4.2, pg 18, line 49 – needs work

- Recommended Text: “The MPDU at the output of the MAC layer passes through the PHY layer and becomes PSDU at the output of the PHY layer after being processed via the various PHY blocks such as channel coding and line coding”

4.5.4.3, pg 19, line 6 – ok

4.5.4.4, pg 19, line 30 – ok

# T-CID 38: MPDU entries in clause 5

5.2.1, pg 26, line 49 – “ supports transfer of data between the MAC sublayer and the PHY”

5.2.1.1, pg 27, line 10 – “requests transfer of data from the MAC sublayer to form a PSDU at the local PHY entity”

5.2.1.1.1, pg 27, line 40 – change MPDU to PPDU

5.2.1.2 pg 27, line 49 – change MPDU to PPDU , delete rest of sentence after transmission

5.2.1.3. pg 28, line 38 – change MPDU to data

5.2.1.3.2, pg 29, line 23 – change MPDU to data

Figure 21, pg 36, line 10 – change MPDU to PSDU. Change PDUs in pg 36 to PSDUs

## T-CID 51 – Suggested remedy- Add text

Add “The SIFS, LIFS and RIFS period is based on the currently negotiated optical clock rate by the MAC before starting data communication. Once the optical clock rate is selected, the SIFS, LIFS and RIFS period is fixed to the values shown in Table 5.”.

Change “symbols” in Table 5 to “Optical Clock Rate”

# T-CID 63 – Assignment

Accepted in principle. Three action items here (assigned to Sridhar) ...

1. Split option field into 4 fields for OOK and 1 CES field for PHY III

2. Answer the question "does dimmed OOK apply to PHY III

3. Clarify text to indicate that the CES option field is turned on by reading the MCS ID.

## T-CID 63 - Resolution

Split Figure 23 into Figure 23 (a) and Figure 23 (b)


Add following text on Pg 37, line 16

- The options field in Figure 23 (a) shall be transmitted only if the dimmed OOK bit is set in the PHR.
- The options field in Figure 23 (b) shall be transmitted only if PHY III is selected based on the MCS ID chosen in the PHR.
- The dimmed OOK mode shall not be used with PHY III. i.e. both the option fields shall never be used simultaneously.




# T-CID 70, 72

(a) Output from PHY SAP



(b) Output from OPTICAL SAP



## T-CID 70, 72

In the receiver side, ADC for PHY III should have at least 4 over times sampling rate to symbol rate.

For avoiding the degradation, the delay difference should be smaller than a half of the sampling period.

As a result, the allowable delay difference is  $1/8$  of the symbol duration. So,  $\Delta$  should be less than 12.5% of symbol clock.

## Recommendation for T-CID 70, 72

Add subclause 5.1.x for “Maximum error tolerance for multiple optical sources”

Suggested text:

- If multiple optical sources are used, it is recommended the optical sources have similar frequency responses in order to assist communication. The input to all the optical sources from the PHY shall be synchronized. The error at the output of the optical sources shall not vary by more than 12.5%
- Add figure (optional – per committee decision)