
IEEE P802.15
Wireless Personal Area Networks

| | | | |
|----------------|---|---|--|
| Project | IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs) | | |
| Title | Proposed Editorial Reorganization of IEEE802.15.7 Draft | | |
| Date Submitted | November 2010 | | |
| Source | Rick Roberts Intel Labs | Voice: [] Fax: [] E-mail: richard.d.roberts@intel.com | |
| Re: | | | |
| Abstract | | | |
| Purpose | | | |
| Notice | This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein. | | |
| Release | The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15. | | |

This document proposes an editorial reorganization of the IEEE802.15.7 draft, following the format of IEEE802.15.4i, to improve readability and maintenance.

The proposed reorganization would actually be done after comment resolution but before the issuance of D4.

A test reorganization was done using draft D3 (TOC shown starting on page 3 of this document) and no problems were encountered; that is, there were no indications of broken reference links and the document printed just fine.

The actual reorganization would be done in the same manner and takes about 2 hours to do.

Editorially reorganized TOC

- 1. Overview.....1
 - 1.1 Scope1
 - 1.2 Purpose.....1
- 2. References.....1
- 3. Definitions1
- 4. Acronyms and abbreviations.....4
- 5. General description6
 - 5.1 Introduction6
 - 5.2 Network topologies8
 - 5.2.1 Peer-to-peer topology8
 - 5.2.2 Star topology8
 - 5.2.3 Broadcast topology8
 - 5.3 Modulation domain spectrum.....8
 - 5.4 Architecture9
 - 5.4.1 PHY layer10
 - 5.4.1.1 PHY frame structure11
 - 5.4.1.2 Interoperability and co-existence between PHY types11
 - 5.4.2 MAC sublayer12
 - 5.4.3 Dimming and flicker mitigation support13
 - 5.4.3.1 Light dimming14
 - 5.4.3.1.1 Idle pattern and compensation time dimming14
 - 5.4.3.1.2 Visibility pattern dimming14
 - 5.4.3.1.3 CSK dimming15
 - 5.4.3.1.4 OOK dimming15
 - 5.4.3.1.5 VPPM dimming16
 - 5.4.3.2 Flicker mitigation.....17
 - 5.4.3.2.1 Intra-frame flicker mitigation18
 - 5.4.3.2.2 Inter-frame flicker mitigation18
 - 5.5 Functional overview18
 - 5.5.1 Superframe structure18
 - 5.5.2 Data transfer model19
 - 5.5.2.1 Data transfer to a coordinator19
 - 5.5.2.2 Data transfer from a coordinator.....20
 - 5.5.2.3 Peer-to-peer data transfers22
 - 5.5.3 Clock rate selection22
 - 5.5.4 Frame structure22

Introduction is the same as before.

- 5.5.4.1 Beacon frame23
- 5.5.4.2 Data frame23
- 5.5.4.3 Acknowledgment frame.....23
- 5.5.4.4 MAC command frame24
- 5.5.4.5 CVD frame24
- 5.5.5 Improving probability of successful delivery24
 - 5.5.5.1 Random access mechanism24
 - 5.5.5.2 Frame acknowledgment.....25
 - 5.5.5.3 Data verification25
- 5.6 Security.....25
- 5.7 Concept of primitives26

- 6. MAC protocol specification.....28
 - 6.1 MAC functional description28
 - 6.1.1 Channel access.....28
 - 6.1.1.1 Superframe structure.....28
 - 6.1.1.1.1 Contention access period (CAP).....28
 - 6.1.1.1.2 Contention-free period (CFP)28
 - 6.1.1.1.3 Visibility support during channel access32
 - 6.1.1.2 Interframe spacing (IFS).....32
 - 6.1.1.3 Random access algorithm33
 - 6.1.2 Starting a VPAN.....35
 - 6.1.2.1 Scanning through channels35
 - 6.1.2.1.1 Active channel scan36
 - 6.1.2.1.2 Passive channel scan37
 - 6.1.2.2 VPAN initiation38
 - 6.1.2.3 Beacon generation39
 - 6.1.2.4 Device discovery40
 - 6.1.2.5 Guard and aggregation color channels40
 - 6.1.3 Maintaining VPANs41
 - 6.1.3.1 Detection.....41
 - 6.1.3.2 Resolution.....42
 - 6.1.3.3 Realigning a VPAN42
 - 6.1.3.4 Realignment in a VPAN42
 - 6.1.3.5 Updating superframe configuration and channel PIB attributes.....43
 - 6.1.4 Association and disassociation43
 - 6.1.4.1 Association43
 - 6.1.4.2 Disassociation.....45
 - 6.1.5 Synchronization.....46
 - 6.1.5.1 Synchronization with beacons46
 - 6.1.5.2 Synchronization without beacons47
 - 6.1.6 Transaction handling47
 - 6.1.7 Transmission, reception, and acknowledgment.....48
 - 6.1.7.1 Transmission.....48
 - 6.1.7.2 Reception and rejection49
 - 6.1.7.3 Extracting pending data from a coordinator51
 - 6.1.7.4 Use of acknowledgments and retransmissions52
 - 6.1.7.4.1 No acknowledgment52
 - 6.1.7.4.2 Acknowledgment52

MAC starts with functional description which will help the reader understand the rest of the text.

| | | |
|-----------|--|----|
| 6.1.7.4.3 | Retransmissions | 53 |
| 6.1.7.5 | Transmission scenarios | 54 |
| 6.1.8 | GTS allocation and management | 54 |
| 6.1.8.1 | CAP maintenance | 56 |
| 6.1.8.2 | GTS allocation | 56 |
| 6.1.8.3 | GTS usage | 57 |
| 6.1.8.4 | GTS deallocation | 57 |
| 6.1.8.5 | GTS reallocation | 58 |
| 6.1.8.6 | GTS expiration | 60 |
| 6.1.9 | Fast link recovery | 60 |
| 6.1.10 | Multiple channel resource assignment | 64 |
| 6.1.10.1 | Multiple channel information | 64 |
| 6.1.10.2 | Band hopping for interference avoidance | 66 |
| 6.1.11 | VLC cell design and mobility support | 67 |
| 6.1.11.1 | Mobility using boundary information | 68 |
| 6.1.11.2 | Cell configuration during superframe | 69 |
| 6.1.11.3 | Cell size and location search procedure | 70 |
| 6.1.12 | Color function support | 71 |
| 6.1.12.1 | CVD frame usage for MAC state indication | 71 |
| 6.1.12.2 | CVD frame usage for file-transfer status indication | 73 |
| 6.1.12.3 | CVD frame usage for channel quality indication | 73 |
| 6.1.12.4 | CVD frame usage for acknowledgment indication | 74 |
| 6.1.13 | Color-stabilization | 74 |
| 6.1.14 | Visibility and dimming support | 75 |
| 6.1.14.1 | Visibility pattern | 75 |
| 6.1.14.2 | Extended preamble mode for visibility | 75 |
| 6.1.14.3 | Transmitting visibility pattern during uplink for star topology mode | 76 |
| 6.1.14.4 | Dimming override capability | 78 |
| 6.1.14.5 | PWM signal override | 78 |
| 6.1.14.6 | MAC layer transmission adjustment for dimming | 79 |
| 6.1.14.7 | Device discovery and association in the presence of dimming and visibility | 79 |
| 6.1.14.8 | Link adaptation for dimming support | 80 |
| 6.2 | MAC frame formats | 81 |
| 6.2.1 | General MAC frame format | 81 |
| 6.2.1.1 | Frame control field | 82 |
| 6.2.1.1.1 | Frame version subfield | 82 |
| 6.2.1.1.2 | Frame type subfield | 82 |
| 6.2.1.1.3 | Security enabled subfield | 83 |
| 6.2.1.1.4 | Frame pending subfield | 83 |
| 6.2.1.1.5 | Acknowledgment request subfield | 83 |
| 6.2.1.1.6 | Destination addressing mode subfield | 83 |
| 6.2.1.1.7 | Source addressing mode subfield | 83 |
| 6.2.1.2 | Sequence number field | 84 |
| 6.2.1.3 | Destination VPAN identifier field | 84 |
| 6.2.1.4 | Destination address field | 84 |
| 6.2.1.5 | Source VPAN identifier field | 85 |
| 6.2.1.6 | Source address field | 85 |
| 6.2.1.7 | Auxiliary security header field | 85 |
| 6.2.1.8 | Frame payload field | 85 |
| 6.2.1.9 | FCS field | 85 |

| | | |
|-----------|--|-----|
| 6.2.2 | Format of individual frame types | 85 |
| 6.2.2.1 | Beacon frame format | 85 |
| 6.2.2.1.1 | Beacon frame MHR fields | 85 |
| 6.2.2.1.2 | Superframe specification field | 86 |
| 6.2.2.1.3 | GTS specification field | 87 |
| 6.2.2.1.4 | GTS directions field..... | 87 |
| 6.2.2.1.5 | GTS list field..... | 88 |
| 6.2.2.1.6 | Pending address specification field..... | 88 |
| 6.2.2.1.7 | Address list field | 88 |
| 6.2.2.1.8 | Beacon payload field | 89 |
| 6.2.2.2 | Data frame format..... | 89 |
| 6.2.2.2.1 | Data frame MHR fields..... | 89 |
| 6.2.2.2.2 | Data payload field..... | 89 |
| 6.2.2.3 | Acknowledgment frame format | 90 |
| 6.2.2.4 | Command frame format..... | 91 |
| 6.2.2.4.1 | MAC command frame MHR fields | 91 |
| 6.2.2.4.2 | Command frame Identifier field | 92 |
| 6.2.2.5 | Command payload field..... | 92 |
| 6.2.2.6 | CVD frame format | 93 |
| 6.2.2.7 | Capabilities IE | 93 |
| 6.2.2.7.1 | Capability information Field..... | 93 |
| 6.2.2.7.2 | Aggregation and guard channel | 97 |
| 6.2.2.8 | Wavelength quality indication IE | 98 |
| 6.3 | MAC Command frames..... | 98 |
| 6.3.1 | Association request command | 98 |
| 6.3.1.1 | MHR fields | 100 |
| 6.3.2 | Association response command..... | 100 |
| 6.3.2.1 | MHR fields | 100 |
| 6.3.2.2 | Short address field | 101 |
| 6.3.2.3 | Association status field..... | 101 |
| 6.3.3 | Disassociation notification command..... | 101 |
| 6.3.3.1 | MHR fields | 101 |
| 6.3.3.2 | Disassociation reason field | 102 |
| 6.3.4 | Data request command | 102 |
| 6.3.5 | VPAN ID conflict notification command..... | 103 |
| 6.3.6 | Beacon request command..... | 104 |
| 6.3.7 | Coordinator realignment command | 104 |
| 6.3.7.1 | MHR fields | 105 |
| 6.3.7.2 | VPAN identifier field | 105 |
| 6.3.7.3 | Coordinator short address field..... | 105 |
| 6.3.7.4 | Logical channel field | 105 |
| 6.3.7.5 | Short address field | 105 |
| 6.3.8 | GTS request command | 106 |
| 6.3.8.1 | MHR fields | 106 |
| 6.3.8.2 | GTS characteristics field..... | 106 |
| 6.3.9 | Blinking notification command..... | 107 |
| 6.3.10 | Dimming notification command..... | 107 |
| 6.3.11 | Fast link recovery command..... | 107 |
| 6.3.12 | Mobility notification command | 108 |
| 6.3.13 | GTS response command..... | 108 |

- 6.3.13.1 MHR fields109
- 6.3.13.2 GTS characteristics field.....109
- 6.3.14 Clock rate change notification command109
- 6.3.15 Multiple channel assignment command110
- 6.3.16 Color stabilization timer notification command110
- 6.3.17 Color stabilization information command110
- 6.3.18 CVD disable command.....111
- 7. MAC sublayer service specification112
 - 7.1 Overview112
 - 7.2 MAC data service.....112
 - 7.2.1 MCPS-DATA.request112
 - 7.2.1.1 Appropriate usage.....115
 - 7.2.1.2 Effect on receipt.....115
 - 7.2.2 MCPS-DATA.confirm116
 - 7.2.2.1 When generated117
 - 7.2.2.2 Appropriate usage.....117
 - 7.2.3 MCPS-DATA.indication117
 - 7.2.3.1 When generated120
 - 7.2.3.2 Appropriate usage.....120
 - 7.2.4 MCPS-PURGE.request120
 - 7.2.4.1 Appropriate usage.....120
 - 7.2.4.2 Effect on receipt.....121
 - 7.2.5 MCPS-PURGE.confirm121
 - 7.2.5.1 When generated121
 - 7.2.5.2 Appropriate usage.....121
 - 7.2.6 Data service message sequence chart121
 - 7.3 MAC management service122
 - 7.3.1 Association primitives123
 - 7.3.1.1 MLME-ASSOCIATE.request123
 - 7.3.1.1.1 Appropriate usage.....124
 - 7.3.1.1.2 Effect on receipt.....124
 - 7.3.1.2 MLME-ASSOCIATE.indication125
 - 7.3.1.2.1 When generated126
 - 7.3.1.2.2 Appropriate usage.....126
 - 7.3.1.3 MLME-ASSOCIATE.response126
 - 7.3.1.3.1 Appropriate usage.....127
 - 7.3.1.3.2 Effect on receipt.....127
 - 7.3.1.4 MLME-ASSOCIATE.confirm128
 - 7.3.1.4.1 When generated130
 - 7.3.1.4.2 Appropriate usage.....130
 - 7.3.1.5 Association message sequence charts.....131
 - 7.3.2 Disassociation primitives.....131
 - 7.3.2.1 MLME-DISASSOCIATE.request131
 - 7.3.2.1.1 Appropriate usage.....133
 - 7.3.2.1.2 Effect on receipt.....133
 - 7.3.2.2 MLME-DISASSOCIATE.indication.....134
 - 7.3.2.2.1 When generated135
 - 7.3.2.2.2 Appropriate usage.....135

MAC services are a separate section.

| | | |
|-----------|---|-----|
| 7.3.2.3 | MLME-DISASSOCIATE.confirm | 135 |
| 7.3.2.3.1 | When generated | 135 |
| 7.3.2.3.2 | Appropriate usage | 136 |
| 7.3.2.4 | Disassociation message sequence charts | 137 |
| 7.3.3 | Beacon notification primitive | 137 |
| 7.3.3.1 | MLME-BEACON-NOTIFY.indication..... | 137 |
| 7.3.3.1.1 | When generated | 140 |
| 7.3.3.1.2 | Appropriate usage | 140 |
| 7.3.4 | Primitives for reading PIB attributes | 140 |
| 7.3.4.1 | MLME-GET.request..... | 140 |
| 7.3.4.1.1 | Appropriate usage | 141 |
| 7.3.4.1.2 | Effect on receipt..... | 141 |
| 7.3.4.2 | MLME-GET.confirm..... | 141 |
| 7.3.4.2.1 | When generated | 141 |
| 7.3.4.2.2 | Appropriate usage | 141 |
| 7.3.5 | GTS management primitives | 142 |
| 7.3.5.1 | MLME-GTS.request..... | 142 |
| 7.3.5.1.1 | Appropriate usage | 142 |
| 7.3.5.1.2 | Effect on receipt..... | 143 |
| 7.3.5.2 | MLME-GTS.indication | 144 |
| 7.3.5.2.1 | When generated | 144 |
| 7.3.5.2.2 | Appropriate usage | 146 |
| 7.3.5.3 | MLME-GTS.confirm..... | 146 |
| 7.3.5.3.1 | When generated | 146 |
| 7.3.5.3.2 | Appropriate usage | 147 |
| 7.3.5.4 | GTS management message sequence charts..... | 147 |
| 7.3.6 | Primitives for resetting the MAC sublayer | 147 |
| 7.3.6.1 | MLME-RESET.request | 147 |
| 7.3.6.1.1 | Appropriate usage | 148 |
| 7.3.6.1.2 | Effect on receipt..... | 148 |
| 7.3.6.2 | MLME-RESET.confirm | 149 |
| 7.3.6.2.1 | When generated | 149 |
| 7.3.6.2.2 | Appropriate usage | 149 |
| 7.3.7 | Primitives for specifying the receiver enable time | 149 |
| 7.3.7.1 | MLME-RX-ENABLE.request..... | 149 |
| 7.3.7.1.1 | Appropriate usage | 150 |
| 7.3.7.1.2 | Effect on receipt..... | 150 |
| 7.3.7.2 | MLME-RX-ENABLE.confirm..... | 151 |
| 7.3.7.2.1 | When generated | 151 |
| 7.3.7.2.2 | Appropriate usage | 152 |
| 7.3.7.3 | Message sequence chart for changing the state of the receiver | 152 |
| 7.3.8 | Primitives for channel scanning | 153 |
| 7.3.8.1 | MLME-SCAN.request..... | 153 |
| 7.3.8.1.1 | Appropriate usage | 154 |
| 7.3.8.1.2 | Effect on receipt..... | 154 |
| 7.3.8.2 | MLME-SCAN.confirm..... | 155 |
| 7.3.8.2.1 | When generated | 155 |
| 7.3.8.2.2 | Appropriate usage | 155 |
| 7.3.8.3 | Channel scan message sequence charts | 156 |
| 7.3.9 | Communication status primitive..... | 156 |

| | | |
|------------|---|-----|
| 7.3.9.1 | MLME-COMM-STATUS.indication | 156 |
| 7.3.9.1.1 | When generated | 159 |
| 7.3.9.1.2 | Appropriate usage | 160 |
| 7.3.10 | Primitives for writing PIB attributes..... | 160 |
| 7.3.10.1 | MLME-SET.request | 160 |
| 7.3.10.1.1 | Semantics of the primitive | 160 |
| 7.3.10.1.2 | Appropriate usage | 160 |
| 7.3.10.1.3 | Effect on receipt..... | 160 |
| 7.3.10.2 | MLME-SET.confirm | 161 |
| 7.3.10.2.1 | When generated | 162 |
| 7.3.10.2.2 | Appropriate usage | 162 |
| 7.3.11 | Primitives for updating the superframe configuration..... | 162 |
| 7.3.11.1 | MLME-START.request..... | 162 |
| 7.3.11.1.1 | Appropriate usage | 164 |
| 7.3.11.1.2 | Effect on receipt..... | 164 |
| 7.3.11.2 | MLME-START.confirm..... | 165 |
| 7.3.11.2.1 | When generated | 166 |
| 7.3.11.2.2 | Appropriate usage | 166 |
| 7.3.11.3 | Message sequence chart for updating the superframe configuration..... | 166 |
| 7.3.12 | Primitives for synchronizing with a coordinator | 166 |
| 7.3.12.1 | MLME-SYNC.request..... | 167 |
| 7.3.12.1.1 | Appropriate usage | 168 |
| 7.3.12.1.2 | Effect on receipt..... | 168 |
| 7.3.13 | Primitives for synchronization loss with a coordinator | 168 |
| 7.3.13.1 | MLME-SYNC-LOSS.indication | 168 |
| 7.3.13.2 | Message sequence chart for synchronizing with a coordinator | 170 |
| 7.3.13.2.1 | When generated | 170 |
| 7.3.13.2.2 | Appropriate usage | 172 |
| 7.3.14 | Primitives for requesting data from a coordinator | 172 |
| 7.3.14.1 | MLME-POLL.request | 172 |
| 7.3.14.1.1 | Appropriate usage | 173 |
| 7.3.14.1.2 | Effect on receipt..... | 173 |
| 7.3.14.2 | MLME-POLL.confirm | 174 |
| 7.3.14.2.1 | When generated | 174 |
| 7.3.14.2.2 | Appropriate usage | 174 |
| 7.3.14.3 | Message sequence chart for requesting data from a coordinator..... | 175 |
| 7.4 | MAC constants and PIB attributes | 175 |
| 7.4.1 | MAC constants | 175 |
| 7.4.2 | MAC PIB attributes | 175 |
| 7.5 | Optical clock rate selection | 184 |
| 7.5.1 | Optical clock rate selection for P2P topology | 184 |
| 7.5.1.1 | Explicit notification | 185 |
| 7.5.1.2 | Without explicit notification..... | 186 |
| 7.5.2 | Optical clock rate selection for star topology | 187 |
| 7.5.2.1 | Explicit notification | 187 |
| 7.5.2.2 | Without explicit notification..... | 188 |
| 7.5.3 | Clock rate selection for multicast topology | 189 |
| 7.5.3.1 | Explicit notification | 189 |
| 7.5.3.2 | Without explicit notification..... | 191 |
| 7.6 | Message sequence charts illustrating MAC-PHY interaction | 191 |

8. Security suite specifications.....200

8.1 Overview200

8.2 Functional description200

8.2.1 Outgoing frame security procedure200

8.2.2 Outgoing frame key retrieval procedure.....201

8.2.3 Incoming frame security procedure202

8.2.4 Incoming frame security material retrieval procedure.....204

8.2.5 Keydescriptor lookup procedure205

8.2.6 Blacklist checking procedure.....205

8.2.7 Device descriptor lookup procedure.....206

8.2.8 Incoming security level checking procedure206

8.2.9 Incoming key usage policy checking procedure.....207

8.3 Security operations207

8.3.1 Integer and octet representation.....207

8.3.2 CCM* nonce.....207

8.3.3 CCM* prerequisites207

8.3.4 CCM* transformation data representation.....208

8.3.4.1 Key and nonce data inputs.....208

8.3.4.2 a data and m data208

8.3.4.3 c data output.....209

8.3.5 CCM* inverse transformation data representation209

8.3.5.1 Key and nonce data inputs.....209

8.3.5.2 c data and a data.....209

8.3.5.3 m data output209

8.4 Auxiliary security header210

8.4.1 Integer and octet representation.....210

8.4.2 Security control field210

8.4.2.1 Security level subfield211

8.4.2.2 Key identifier mode subfield212

8.4.3 Frame counter field.....212

8.4.4 Key identifier field212

8.4.4.1 Key source subfield213

8.4.4.2 Key index subfield.....213

8.5 Security-related MAC PIB attributes213

8.5.1 PIB security material213

8.5.2 Key table.....216

8.5.3 Device table217

8.5.4 Minimum security level table217

8.5.5 Frame counter217

8.5.6 Automatic request attributes217

8.5.7 Default key source.....217

8.5.8 Coordinator address.....218

9. General PHY layer requirements218

9.1 Overview218

9.2 Operating modes.....218

9.3 General requirements.....218

9.3.1 Wavelength band plan220

Security is its own section.

The general PHY requirements are their own section.

- 9.3.2 Optical mapping221
- 9.3.3 Maximum error tolerance for multiple optical sources.....221
- 9.3.4 Minimum LIFS, SIFS and RIFS periods221
- 9.3.5 TX-to-RX turnaround time221
- 9.3.6 RX-to-TX turnaround time221
- 9.3.7 Transmit data clock frequency tolerance222
- 9.3.8 Wavelength quality indicator (WQI).....222
 - 9.3.8.1 OOK and VPPM WQI support.....222
 - 9.3.8.2 CSK wavelength quality indication support222
- 9.3.9 Clear channel assessment (CCA).....222
- 9.4 Data modes223
- 9.5 Dimming and flicker mitigation224
 - 9.5.1 Dimming during idle time224
 - 9.5.1.1 Idle pattern and compensation time dimming.....224
 - 9.5.1.2 Visibility pattern dimming224
 - 9.5.2 Dimming during data transmission time.....225
 - 9.5.2.1 CSK-mode dimming226
 - 9.5.2.2 OOK-mode dimming226
 - 9.5.2.3 VPPM-mode dimming226
 - 9.5.3 Flicker mitigation226
 - 9.5.4 CSK color stabilization at the transmitter226
- 9.6 PPDU format228
 - 9.6.1 Preamble field.....228
 - 9.6.2 PHY header230
 - 9.6.2.1 Burst mode.....230
 - 9.6.2.2 Channel number.....230
 - 9.6.2.3 MCS ID231
 - 9.6.2.4 Length of PSDU field232
 - 9.6.2.5 Dimmed OOK extension232
 - 9.6.3 HCS233
 - 9.6.4 Optional fields233
 - 9.6.4.1 Tail bits233
 - 9.6.4.2 Compensation length233
 - 9.6.4.3 Resync length233
 - 9.6.4.4 Subframe length and generation233
 - 9.6.4.5 Optional field check sequence generation234
 - 9.6.4.6 Channel estimation sequence.....234
 - 9.6.5 PSDU field234
- 10. PHY service specifications235
 - 10.1 Overview235
 - 10.2 PHY management service235
 - 10.2.1 PLME-CCA.request237
 - 10.2.1.1 When generated237
 - 10.2.1.2 Effect on receipt.....237
 - 10.2.2 PLME-CCA.confirm237
 - 10.2.2.1 When generated237
 - 10.2.2.2 Effect on receipt.....237
 - 10.2.3 PLME-GET.request.....237

PHY services are their own section.

- 10.2.3.1 Appropriate usage.....238
- 10.2.3.2 Effect on receipt.....238
- 10.2.4 PLME-GET.confirm.....238
 - 10.2.4.1 When generated.....239
 - 10.2.4.2 Effect on receipt.....239
- 10.2.5 PLME-SET.request239
 - 10.2.5.1 When generated.....239
 - 10.2.5.2 Effect on receipt.....239
- 10.2.6 PLME-SET.confirm239
 - 10.2.6.1 When generated.....240
 - 10.2.6.2 Effect on receipt.....240
- 10.2.7 PLME-SET-TRX-STATE.request240
 - 10.2.7.1 When generated.....241
 - 10.2.7.2 Effect on receipt.....241
- 10.2.8 PLME-SET-TRX-STATE.confirm241
 - 10.2.8.1 When generated.....242
 - 10.2.8.2 Effect on receipt.....242
- 10.2.9 PLME-SWITCH.request242
 - 10.2.9.1 When generated.....242
 - 10.2.9.2 Effect on receipt.....243
- 10.2.10 PLME-SWITCH.confirm243
 - 10.2.10.1 When generated.....243
 - 10.2.10.2 Effect on receipt.....243
- 10.3 PHY data service243
 - 10.3.1 PD-DATA.request.....244
 - 10.3.1.1 When generated.....244
 - 10.3.1.2 Effect on receipt.....244
 - 10.3.2 PD-DATA.confirm.....244
 - 10.3.2.1 When generated.....245
 - 10.3.2.2 Effect on receipt.....245
 - 10.3.3 PD-DATA.indication.....245
 - 10.3.3.1 When generated.....245
 - 10.3.3.2 Effect on receipt.....245
- 10.4 PHY enumerations description.....246
- 10.5 PHY constants246
 - 10.5.1 PHY constants247
- 10.6 PHY PIB attributes247
- 11. PHY I specifications248
 - 11.1 Reference modulator diagram248
 - 11.2 Outer forward error correction encoder.....248
 - 11.3 Interleaving and puncturing block.....248
 - 11.4 Inner forward error correction encoder248
 - 11.4.1 Rate 1/4 convolutional code251
 - 11.4.2 Rate 1/3 convolutional code251
 - 11.4.3 Rate 2/3 convolutional code251
 - 11.5 Run-length limiting encoder.....252
 - 11.5.1 4B6B encoding for VPPM modes252
 - 11.5.2 Manchester encoding for OOK mode.....254

Each PHY type is its own section which makes it easy to add additional PHYs.

| | |
|--|-----|
| 12. PHY II specifications | 254 |
| 12.1 Reference modulator diagram | 254 |
| 12.2 Forward error correction encoder | 254 |
| 12.3 Run-length limiting encoder | 255 |
| 13. PHY III specifications | 255 |
| 13.1 Reference modulator diagram | 255 |
| 13.2 Scrambler | 256 |
| 13.3 Channel encoder | 257 |
| 13.4 CSK constellation overview | 257 |
| 13.5 CSK constellation design rules | 258 |
| 13.5.1 Design rule for 4-CSK | 258 |
| 13.5.2 Design rule for 8-CSK | 259 |
| 13.5.3 Design rule for 16-CSK | 260 |
| 13.6 Data mapping for CSK | 260 |
| 13.7 Valid color band combinations | 262 |
| 13.8 CSK color mapping | 264 |
| 13.9 CSK calibration at the receiver | 265 |
| Annex A Bibliography | 267 |
| A.1 General | 267 |
| A.2 Regulatory documents | 268 |
| Annex B Service-specific convergence sublayer (SSCS) | 270 |
| B.1 IEEE 802.2 convergence sublayer | 270 |
| B.1.1 MA-UNITDATA.request | 270 |
| B.1.1.1 Appropriate usage | 271 |
| B.1.1.2 Effect on receipt | 271 |
| B.1.2 MA-UNITDATA.indication | 271 |
| B.1.2.1 When generated | 272 |
| B.1.2.2 Appropriate usage | 272 |
| B.1.3 MA-UNITDATA-STATUS.indication | 272 |
| B.1.3.1 When generated | 272 |
| B.1.3.2 Appropriate usage | 273 |
| Annex C Cyclic redundancy check | 274 |
| Annex D Channel assignment | 275 |
| Annex E -Considerations for VLC using LED displays | 281 |
| E.1 Introduction - Dynamic displays vs. addressed displays | 281 |
| E.2 Dynamic displays | 281 |
| E.2.1 Operation mechanism | 281 |

- E.2.2 Reduced brightness mitigation on VLC dynamic displays282
- E.2.3 VLC application using dynamic displays283
- E.3 Addressed displays.....284
 - E.3.1 LCD display LED backlighting modulation284
 - E.3.2 LED pixel modulation284
- Annex F Receiver performance variation on multi-color channels285