

**Project: IEEE P802.15 Working Group for Wireless Personal Area Networks
(WPANs)**

Submission Title: [Resolutions to MR-FSK Comments on filtered FSK]

Date Submitted: [November 2010]

Source: [Steve Shearer, Cristina Seibert] Company [Silver Spring Networks]

Re: [Resolutions to MR-FSK Comments on filtered FSK]

Abstract: [Resolutions to MR-FSK Comments on filtered FSK]

Purpose: [802.15.4g Comment Resolution for LB59.]

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Overview

- Filtered FSK Definition
- Replace GFSK with Filtered FSK
- General Filtered FSK
- Filtered FSK Modulation

Filtered FSK Definition

- CID 24
 - Filtered FSK is used consistently (sic) within Table 1 without any definition of what the level of filtering is
 - Define the filtering level for Filtered FSK modulations
 - A/P Filtering is defined in 6.12a.1, Insert footnote(s) in Table 1 referring to definition in 6.12a.1.
- CID 348
 - The term filtered FSK is not defined previously.
 - There should be a foot note indicating which clause defines the term "filtered FSK" Add a foot note referring (sic) the clause defining the term "Filtered FSK"
 - A/P Same resolution as CID 24

Filtered FSK Definition

- CID 394
 - The first occurrence of the words "filtered FSK" is here, and it has yet to be defined. Definition seems to be at line 52 on page 51 –
 - consider moving
 - A/P Same as CID 24
- CID 1090
 - Reference in Table 1a for MR-FSK PHY modulation scheme references "Filtered x-FSK". This is ambiguous and there is no reference or definition of the filtering parameter and will lead to confusion and may reduce interoperability amongst "compliant" solutions
 - Define both modulation schemes for constant MR-FSK PHYs as FSK (for legacy system implementation) and GFSK with BT = 0.5 or 1.0 for future SUN systems
 - A/P Definition is given in 6.12a.1. Comment withdrawn

Replace GFSK with Filtered FSK

- CID's 360, 361, 368 ,370, 371, 591, 659, 664, 951, 953, 974, 1015, 1018
 - All of the above comments address a similar theme of *“CID 360, FSK/GFSK has been replaced by Filtered FSK”*
 - A/P all, replace with “Filtered FSK” accordingly
- CID 747
 - Since we don't use the term GFSK anymore, we don't need to distinguish between the MR-FSK PHY at 950 MHz and the 15.4d PHYs.
 - The footnotes referencing subclauses 6.11, 6.7 and 6.12a are no longer necessary. Remove the three footnotes from Table 1.
 - Accept

General Filtered FSK

- CID 347
 - The first two modes in the 950 MHz band using GFSK and BPSK are not defined later in the draft. They don't have a corresponding channel page definition in clause 6.1.2.7.2.
 - Add a channel page definition in clause 6.1.2.7.2 and add GFSK and BPSK in the lists of supported modulations, or remove these two modes.
 - A/P These are 4d modes. Remove them from the table.
- CID 507
 - Notation "+" should be placed at the leftmost column (950), rather than at Modulation columns (Filtered 2FSK), in order for OFDM and O-QPSK PHYs to be applicable to this note.
 - Change as proposed
 - Accept, modify text accordingly
- CID 548
 - It is suggested to use $1/3$ instead of 0.33 ($1/3$ is used elsewhere in the text).
 - Change mod index = 0.33 to mod index = $1/3$.
 - Accept , modify text accordingly
- CID 602
 - GFSK/FSK into 2FSK and 4FSK in Table 125b.
 - Change as commented
 - Accept , modify text accordingly

Filtered FSK Modulation

- 374
 - The emission limits on M1 and M2 exceeds unfiltered FSK by more than 11dB. Will cause excessive interference in adjacent and alternate channels.
 - Increase both limits by 8dB.
 - A/P Topic was investigated at length and presented in docs 331r8 and 692r0. Current spec is a result of group consensus. No change required.
- 642
 - The filtering for "Filtered 2FSK" and "Filtered 4FSK" is not defined (the spectral mask seems not sufficient, and GFSK is simply a recommendation here for one band ("should be used")).
 - Specify GFSK as the filtering with appropriate band dependant parameters if necessary
 - A/P Same resolution as CID 374.
- 643
 - The spectral mask only applies at two offset frequencies in a 1kHz bandwidth, implying no restriction on emissions at other offsets.
 - Include a full spectral mask with diagram to clearly show limits across a wider range of offset frequencies
 - A/P Same resolution as CID 374.