

January 2014 doc.: IEEE 802.15-14-0025-00-0thz_Information_on_Backhauling_Fronthauling

Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: Information on Backhauling and Fronthauling

Date Submitted: 20 January 2014

Source: Thomas Kürner Company TU Braunschweig

Address Schleinitzstr. 22, D-38092 Braunschweig, Germany

Voice:+495313912416, FAX: +495313915192, E-Mail: t.kuerner@tu-bs.de

Re: doc. 15-13-0636-01-0thz, doc. 15-13-0692-01-0thz

Abstract: Wireless backhauling/fronthauling is one of the potential applications for a standard on 100G. This documents contains information to answer some questions in doc. 15-13-0692-01-0thz, which have been raised during the discussion on doc. 15-13-0636-01-0thz

Purpose: Information of IEEE 802.15 SG 100G

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Information on Backhauling/Fronthauling

Thomas Kürner
TU Braunschweig

Scope

- This documents provides additional information on backhauling and fronthauling addressing some questions raised during discussion on doc. on doc. 15-13-0636-01-0thz.
- The information is based on the references given at the end of the document.

CPRI (Common Public Interface) [1]

- CPRI™ ; publicly available specification for the key internal interface of radio base stations between the Radio Equipment Control (REC) and the Radio Equipment (RE).
- The Parties cooperating to define the CPRI Specification are Ericsson, Huawei, NEC, NSN and Alcatel-Lucent. Nortel contributed to thge first versions of CPRI
- The most recent version is version 6.0 including also LTE Advanced (LTE-A).

CPRI Specification Overview [1]

- The interface is a digitized and serial internal base station interface.
- The necessary items for transport, connectivity and control are included in the Specification. This includes User Plane data, Control Plane transport mechanisms, and means for synchronisation
- The Specification covers Layers 1 and 2 of the OSI stack.
 - The physical layer (layer 1) supports both an electrical interface (i.e. what is used in traditional base stations), and an optical interface (e.g. for base stations with remote radio equipment).
 - Layer 2 supports flexibility and scalability
 - The specifications can be downloaded from [1].

Ongoing Discussions on Fronthaul Service Case Studies [2]

- In [2] the term fronthaul service (managed CPRI) is introduced.
- Three basic models to explain fronthaul services are created and discussed:
 - Case 1: Fronthaul is carried natively over a dark fiber or a transport service. *Maintains the current concept.*
 - Case 2: Pseudo“ CPRI service: RE and REC continue to use CPRI as the interface but transport is achieved through Carrier Ethernet. *This would require a new CPRI/CE interface*
 - Case 3: Evolution of the RE and REC and replacement of CPRI by an Ethernet port. *This would require new developments into the RAN equipment with a longer roadmap.*

CPRI Line Rates

- According to CPRI V6.0 [3], which includes the requirements for LTE-A the following line rates are defined:
 - CPRI line bit rate option 1: 614.4 Mbit/s
 - CPRI line bit rate option 2: 1228.8 Mbit/s
 - CPRI line bit rate option 3: 2457.6 Mbit/s
 - CPRI line bit rate option 4: 3072.0 Mbit/s
 - CPRI line bit rate option 5: 4915.2 Mbit/s
 - CPRI line bit rate option 6: 6144.0 Mbit/s
 - CPRI line bit rate option 7: 9830.4 Mbit/s
 - CPRI line bit rate option 8: 10137.6 Mbit/s

Required Data Rate for Small Cell Backhaul

- In the literature the following indications for required data rates are given:
 - A 2.4 Gb/s GPON (Gigabit enabled Passive Optical Network) is shared among 16 small cells [4].
 - In [5] a range of 10 – 500 Mbps for the required backhaul capacity per small cell is given
- The above numbers are given for current cellular standards.
 - Future standards will provide higher data rates
 - Small cells may become more popular, which may yield the requirement of aggregated backhauling for more than 16 small cells

Required Data Rate for Macro Cell Backhaul and Fronthaul

- [5] gives also some indications on the required capacity for macro cell backhaul and fronthaul.
- The highest numbers are given for the C-RAN case:
 - Backhaul: > 10 Gbps
 - Fronthaul: 1-10 Gbps

References

- [1] <http://www.cpri.info> (visited on 18.1.14)
- [2] <http://backhaulforum.com/front-haul-service-use-cases/> (visited on 17.1.14)
- [3] CPRI Specification V6.0 (30.8.2013)
- [4] C. Ranaweera et. al, „Design and Optimization of Fiber Opic Small-Cell Backhaul Based on an Existing Fiber-to-the-Node Residential Access Network
- [5] <http://backhaulforum.com/cloud-ran-fronthaul-perspective/> (visited on 17.1.14). IEEE Comunicatiosn Magazine, September 2013, pp. 62-69

Technical Expectations Document (TED)

All information contained in this presentation is meant to be included in the technical expectations document 15-11-0745-13-0thz-thz-ig-technical-expectations-document-ted.doc.