Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: What is Optical Camera Communications (OCC)Date Submitted: January 2015Source: Rick RobertsCompany: Intel LabsAddressVoice: 503-712-5012E-Mail: richard.d.roberts@intel.com

Re:

Abstract:

Purpose:

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.


Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Optical Camera Communications (OCC)

A Pragmatic Form of Visible Light Communications

OCC is modulating an LED light with data bits that can be received by a camera, which then decodes the bits and extracts the data.





Today we have millions of mobile devices enabled to receive visible light communications via the camera, but we lack standards to describe the modulation format.

This contribution discusses some OCC topics of interest.

Some Use Cases





Line of Sight Marketing



Provides low cost, beneficial, augmented reality user experience

Submission

January 2015


Basic idea:

- each LED sign uses OCC to broadcast URL info
- multiple parallel transmissions received by camera
- each web page accessed via RAN
- Google Glass displays webpage next to related LED sign
- added information augments users reality

Augmented **Reality**







High Resolution Automobile Positioning



Optical Camera Communications & Photogrammetry Positioning Applications




VLC has a complex ecosystem:

- hinders technology adoption
- simultaneously building out both sides of this ecosystem is difficult
- unlike WiFi, no single source vendor
- A receive side APP solution enables:
- no phone hardware modifications
- simplified ecosystem build out
- millions of potential receivers
- entice VLC enabled LED sources



Standards Will Be Necessary!

But first some basics about electronic cameras



Camera basic components

- Lens ... spatially separates sources
- Image Sensor ... array of photodiode pixels
- Readout Circuit ... convert pixel signal to digital data

Cameras differ on how the pixels are exposed

- Global Shutter ... simultaneously expose all the pixels per frame
- Rolling Shutter ... time sequentially expose each row of pixels per frame




image sensor model: 2 dimensional lightwave-to-digital converter

Sampling rate depends upon how the image sensor does the exposure

- Undersampling (Undersampled Frequency Shift ON-OFF Keying)

- Nyquist Sampling (Picapicamera)

- Rolling Shutter Sampling

Because of camera lens properties, spatial separation of multiple sources is possible enabling MIMO transmission.



Example LED Signage

This LED sign has 321 LEDs ...

- each LED illuminates a unique pixel in the image sensor
- each LED can transmit a unique data stream
- 321 x 321 MIMO !!!

With multiple methods to realize OCC, standards will be necessary. The task group will ...

- explore multiple use cases
- discuss multiple modulation formats
- facilitate complex ecosystem adoption
 - \checkmark via smartphone app
 - \checkmark via modulated LED lights

Some public demos available on the web

1. Under-sampled Frequency Shifted ON-OFF Keying (UFSOOK) (Intel Labs)

http://www.youtube.com/watch?v=K0xsZqTRXes

2. Nyquist Sampled Picapicamera (Casio)

http://www.youtube.com/watch?v=t27x1sztArE

3. Rolling Shutter Sampling (PureVLC)

http://www.youtube.com/watch?v=laxD4SF3jsA